

AC INDUCTION MOTOR DATA SHEET


Model No.or RFQ No.		Item No.		Rev. No. [0]		
Project Name		Project No.		Quantity sets		
GENERAL SPECIFICATION			PERFORMANCE DATA			
Frame Size	160M		Rated Output	11 kW 15 HP		
Type	HS		Number of Poles	2		
Enclosure(Protection)	Totally Enclosed (IP55)		Rotor Type	Squirrel Cage		
Method of Cooling	IC411(FC)		Starting Method*	☐ D.O.L ☐ Y- Δ		
Rated Frequency	60 Hz		Rated Voltage	440 V 380 V 220 V		
Number of Phases	3		Current	Full Load 18.4 A 21.3 A 36.8 A		
Insulation Class	☒ F ☐ B ☐ H		Locked-rotor**	650 % 650 % 650 %		
Temp. Rise at full load (by resistance method)			Efficiency			
at 1.0 S.F 80 deg. C			50% Load 89.7 %			
Motor Location	☒ Indoor ☐ Outdoor		75% Load 90.7 %			
Altitude	Less than 1000 meter		100% Load 90.2 %			
Relative Humidity	Less than 80 %		Power Factor(p.u)			
Ambient Temp.	40 deg. C (Max.)		50% Load 0.800			
Duty Type	Continuous (S1)		75% Load 0.857			
Service Factor	1.15		100% Load 0.870			
Mounting	☒ B3 ☐ B5 ☐ V1 ☐ B3/B5		Speed at Full Load 3535 r.p.m			
Bearing	Type	Anti-Friction	Torque			
	DE/N-DE	6309ZZC3 / 6309ZZC3	Full Load 3.0 kg·m			
	Lubricant	Grease(Polyrex-EM)	Locked-rotor** 180 %			
External Thrust	Not applicable		Breakdown** 250 %			
Coupling Method	☒ Direct ☐ V-Belt		Moment of Inertia (J)			
Shaft Extension	☒ Single ☐ Double		Load(Max.) 2.000 kg·m²			
Terminal Box	Main	☐ Steel ☒ Cast Iron	Motor 0.039 kg·m²			
	Aux.	☐ Yes ☒ No	Sound Pressure Level (No-load & mean value at 1m from motor)			
	Location	Refer to Outline Drawing	79 dB(A)			
Application			Vibration 2.2 mm/sec (r.m.s)			
Area classification	Non-Hazardous		Permissible number of consecutive starts			
Type of Ex-Protection	Not applicable		Cold 3 times			
Applicable Standard	KS,IEC,NEMA MG1 Part30(Vpeak)		Hot 2 times			
ACCESSORIES			Paint	Munsell No.	4.0PB5.4/5.5(VL-451)	
	SUBMITTAL DRAWING					
	Outline Dimension Drawing \ Motor Weight(Approx.)					
	B3	227B2000AB05	117 kg			
	Main T-Box Ass'y	227B8008LA1				
SPARE PARTS			REMARK			
			High Efficiency			
			* For use on PWM VFD 10:1VT, 3:1CT@1.0S.F&F Temp. rise			
		Date	DSND	CHKD	CHKD	APPD
		2011-04-14	W.H.BACK	S. J. RA	O. J. KIM	J. H. KIM

Note: Others not mentioned in this data sheet shall be in accordance with maker standard.
 Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.
 Inspection and performance test shall be maker standard, if not mentioned.
 * In case of Inverter-Fed Motor, performance data is based on sine wave tests.
 ** Data is based on when the motor is supplied at rated voltage & frequency. and the data is expressed as a percentage of full-load value.


Type	:	HS
Full Load Torque	:	3.0 Kg.m
Motor moment of Inertia (J)	:	0.039 Kg.m ²
Load moment of Inertia (J)	:	2.000 Kg.m ²



11 kW		2 P		60 Hz	
Speed at Full Load :				3535 RPM	
Rated Voltage	440V	380V	220V		
Full Load Current	18.4A	21.3A	36.8A		

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F & CURRENT CURVE






NOTE



1.TOLERANCE :

CENTER HEIGHT	160	$\begin{smallmatrix} 0 \\ -0.5 \end{smallmatrix}$
BASE HOLES	$\phi 15$	$\begin{smallmatrix} +0.43 \\ 0 \end{smallmatrix}$
SHAFT DIAMETER	$\phi 42$	$\begin{smallmatrix} +0.018 \\ +0.002 \end{smallmatrix}$
KEYWAY WIDTH	12	$\begin{smallmatrix} 0 \\ -0.043 \end{smallmatrix}$
KEYWAY DEPTH	5	$\begin{smallmatrix} +0.2 \\ 0 \end{smallmatrix}$



CAST IRON CONDUIT BOX

APPD BY	J. H. KIM	UNIT	mm	SUBJECT	KS 160M	CAD PROJ \ FILE
CHKD BY	Y. S. KIM	SCALE	1/8			XSDNKS\B2000AB05
CHKD BY	S. H. KO	PROJEC'N	3rd Angle	TITLE OUTLINE		
DSND BY	I. K. KIM	DATE	2001.10.27			



PT	DESCRIPTION	MATERIAL	DIMENSION	Q'TY
1	CONDUIT BOX	FC15	---	1
2	CONDUIT BOX COVER	FC15	---	1
3	O-RING / COVER	EPDM	φ4	1
4	BOX GASKET	NBR	---	1
5	COVER+BOX HEX BOLT	S45C	M6 X L20	4
6	BOX+FRAME HEX BOLT	S45C	M8 X L20	4
7	GROUND TERMINAL LUG	CU	---	1

PT	"A"	FRAME	REMARK
1	PF 1 1/4"	160FR	---
2	PF 1 1/2"	180FR	---

REV	DATE	CONTENTS	REV'D BY	CHK'D BY	CHK'D BY	APP'D BY
1						

Q'TY	DESCRIPTION	MATERIAL	DIMENSION	WEIGHT	PART NO.	REMARK	NO.
APP'D BY	KIM.Y.S	UNIT	MM				
CHK'D BY	KO.S.H	SCALE	1:1				
CHK'D BY	---	PROJEC'N	3-4# (3rd Angle)				
DSND BY	Y.J.HWANG	DATE	2005.02.16				
TITLE				REF. NO.	227B8008LA	Sheet No. of	
TERMINAL BOX ASSEMBLY				DWG NO.	227B8008LA	Revision No. 0	